

**Cable junction boxes “ Weatherproof ” for encapsulating**



Sealing the cable junction boxes with a fast setting, permanently elastic sealing compound completely prevents the ingress of water and excludes forming of condensation. The sealing compound features outstanding insulation properties. As the compound is transparent, it is possible for visual inspections of the installation to be carried out at anytime.



**Junction boxes**

With metric knockouts and terminal  
Weatherproof: UV-resistant, rainwater-proof, temperature-resistant  
Rated insulation voltage:  $U_i = 690 \text{ V a.c./d.c.}$   
Material: PC-GFS (polycarbonate)  
Colour: grey RAL 7035

**Junction boxes** ทำจาก โพลีคาร์บอเนตที่ผสมเส้นใยแก้ว ทำให้สามารถทนได้ในทุกสภาพอากาศ  
“รุ่นมีรูนิ้ว และ มีเทอร์มินอลด้านใน ที่มาพร้อมกับ กุญชิล้าง”



Part Number	Size (mm)	Sq.mm	Amp Rating	Torque	Terminal	Price (Bath)
WP 0202 G	93x93x62	1.5-2.5 mm <sup>2</sup>	20 A	0.5 Nm		2,974 -.
WP 0402 G	104x104x70	1.5-2.5 mm <sup>2</sup>	20 A	0.5 Nm		3,599 -.
WP 0404 G	104x104x70	1.5-4 mm <sup>2</sup>	32 A	0.7 Nm		3,642 -.
WP 0604 G	130x130x77	1.5-4 mm <sup>2</sup>	32 A	0.7 Nm		4,760 -.
WP 0606 G	130x130x77	2.5-6 mm <sup>2</sup>	40 A	1.5 Nm		4,959 -.
WP 1006 G	180x130x77	2.5-6 mm <sup>2</sup>	40 A	1.5 Nm		6,114 -.
WP 1010 G	180x130x77	4-10 mm <sup>2</sup>	63 A	2.0 Nm		6,330 -.
WP 0202 B	93x93x62	1.5-2.5 mm <sup>2</sup>	20 A	0.5 Nm		2,974 -.
WP 0402 B	104x104x70	1.5-2.5 mm <sup>2</sup>	20 A	0.5 Nm		3,599 -.
WP 0404 B	104x104x70	1.5-4 mm <sup>2</sup>	32 A	0.7 Nm		3,642 -.
WP 0604 B	130x130x77	1.5-4 mm <sup>2</sup>	32 A	0.7 Nm		4,760 -.
WP 0606 B	130x130x77	1.5-6 mm <sup>2</sup>	40 A	1.5 Nm		4,959 -.
WP 1006 B	180x130x77	2.5-6 mm <sup>2</sup>	40 A	1.5 Nm		6,114 -.
WP 1010 B	180x130x77	4-10 mm <sup>2</sup>	63 A	2.0 Nm		6,330 -.

Part Number	Quantity (ml)	Weight (kg)	Price (Bath)
GH 0350	350 ml	0.452 kg	2,715 -.
GH 0500	500 ml	0.608 kg	3,152 -.
GH 0850	850 ml	0.984 kg	3,943 -.
GH 1200	1200 ml	1.321 kg	4,828 -.