

Cable junction boxes “Weatherproof” for outdoor installation



Junction boxes

With metric knockouts and terminal
Weatherproof: UV-resistant, rainwater-proof,
temperature-resistant
Rated insulation voltage: $U_i = 690 \text{ V a.c./d.c.}$
Material: PC-GFS (polycarbonate)
Colour: grey RAL 7035

Part Number	Size (mm)	Sq.mm	Amp Rating	Torque Terminal	Price (Bath)
KF 0202 G	93x93x62	1.5-2.5 mm ²	20 A	0.5 Nm	629 -.
KF 0402 G	104x104x70	1.5-2.5 mm ²	20 A	0.5 Nm	845 -.
KF 0404 G	104x104x70	1.5-4 mm ²	32 A	0.7 Nm	859 -.
KF 0604 G	130x130x77	1.5-4 mm ²	32 A	0.7 Nm	1,231 -.
KF 0606 G	130x130x77	2.5-6 mm ²	40 A	1.5 Nm	1,374 -.
KF 1006 G	180x130x77	2.5-6 mm ²	40 A	1.5 Nm	1,711 -.
KF 1010 G	180x130x77	4-10 mm ²	63 A	2.0 Nm	1,881 -.
KF 1610 G	210x155x92	4-10 mm ²	63 A	2.0 Nm	2,523 -.
KF 1616 G	210x155x92	10-16 mm ²	102 A	3.0 Nm	2,868 -.
KF 2525 G	255x205x112	10-25 mm ²	102 A	3.0 Nm	3,484 -.
KF 3535 G	295x225x122	16-35 mm ²	125 A	12.0 Nm	6,841 -.
KF 5050 G	355x255x122	16-50 mm ²	150 A	12.0 Nm	12,866 -.

Junction boxes ทำจาก โพลีคาร์บอเนตที่ผสมเส้นใยแก้ว ทำให้สามารถทนได้ในทุกสภาพอากาศ
“รุ่นมีรูนิ้วออก และมีเทอร์มินอลด้านใน”



Part Number	Size (mm)	Sq.mm	Amp Rating	Torque Terminal	Price (Bath)	Junction boxes
K 7055	450x300x170	16-50 mm ²	150 A	12.0 Nm	15,906 -.	With metric knockouts and terminal
K 7004	450x300x170	16-70 mm ²	216 A	10.0 Nm	15,385 -.	Rated insulation voltage: $U_i = 690 \text{ V a.c./d.c.}$
K 7005	450x300x170	16-70 mm ²	216 A	10.0 Nm	16,739 -.	Material: PC (polycarbonate)
K 1204	450x300x170	16-150 mm ²	250 A	20.0 Nm	28,418 -.	Colour: grey RAL 7035
K 1205	450x300x170	16-150 mm ²	250 A	20.0 Nm	30,521 -.	
K 2404	600x300x170	25-240 mm ²	400 A	40.0 Nm	36,856 -.	Junction boxes ทำจาก โพลีคาร์บอเนต
K 2405	600x300x170	25-240 mm ²	400 A	40.0 Nm	41,591 -.	“รุ่นมีรูนิ้วออก และมีเทอร์มินอลด้านใน”